

## MODEL C85-12

### CHEST ULTRA LOW FREEZER -40°C TO -85°C

<b>Capacity [ Cu. Ft. ]</b>	<b>12 Cu. Ft.</b>
<b>Capacity [ Liters ]</b>	<b>340 Liters</b>
<b>Temperature Range [ °C ]</b>	<b>-40°C to -85°C</b>
<b>Temperature Range [ °F ]</b>	<b>-40°F to -120°F</b>
Dimensions	Width x Depth x Height
Exterior [ Inches ]	65.5" x 32" x 47.5"
Interior [ Inches ]	55" x 19" x 20"
Exterior [ Centimeters ]	166 x 81 x 120
Interior [ Centimeters ]	139 x 48 x 50
Refrigeration System	Cascade-Style System
Compressors	2, Hermetic Compressors
Air Circulation	Gravity Flow
Defrost Method	Manual
Refrigerant	HCFC & CFC Free
Exterior	Powder Coated Steel
Interior	Zinc Coated Galvanized Steel
Insulation	Polyurethane (Ecomate) Foam
Additional Insulation	Beaded Foam Sub-Lids
Lockable Lid	Lockable with Padlock
Porthole	Optional 1/2"
Casters	6, Swivel with Locks
Storage	Optional Inventory Racks
Shipping Weight	825 Lbs.

#### Electrical

Standard Voltage	115 Volts, 60 Hertz, 1 Phase
Amps / Run Amps / Plug ( Optional Voltages )	20A   15A   NEMA 5-20 208 Volts, 230 Volts
Certification(s)	ETL Listed

#### Controller

Display Type	Microprocessor, Digital
Alarms	High/Low Temp, Power Failure, Low Battery
Alarm Relay	Yes, Dry Contacts
Automatic Restart	Yes, Automatically Restarts After Power Failure
Backup Battery	Yes, Only Powers Alarm

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES



**Warranty** 1 Year Parts & Labor

Specifications subject to change without notice