

MODEL C85-3

CHEST ULTRA LOW FREEZER -40°C TO -85°C

| | |
|---------------------------------|------------------------------|
| Capacity [Cu. Ft.] | 3 Cu. Ft. |
| Capacity [Liters] | 83 Liters |
| Temperature Range [°C] | -40°C to -85°C |
| Temperature Range [°F] | -40°F to -120°F |
| Dimensions | Width x Depth x Height |
| Exterior [Inches] | 34.5" x 25.25" x 48" |
| Interior [Inches] | 24" x 12" x 18" |
| Exterior [Centimeters] | 87 x 64 x 121 |
| Interior [Centimeters] | 61 x 31 x 46 |
| Refrigeration System | Cascade-Style System |
| Compressors | 2, Hermetic Compressors |
| Air Circulation | Gravity Flow |
| Defrost Method | Manual |
| Refrigerant | HCFC & CFC Free |
| Exterior | Powder Coated Steel |
| Interior | Zinc Coated Galvanized Steel |
| Insulation | Polyurethane (Ecomate) Foam |
| Additional Insulation | Beaded Foam Sub-Lids |
| Lockable Lid | Lockable with Padlock |
| Porthole | Optional 1/2" |
| Casters | 4, Swivel with Locks |
| Storage | Optional Inventory Racks |
| Shipping Weight | 500 Lbs. |

Electrical

| | |
|---|---|
| Standard Voltage | 115 Volts, 60 Hertz, 1 Phase |
| Amps / Run Amps / Plug (Optional Voltages) | 15A 13A NEMA 5-15 208 Volts, 230 Volts |
| Certification(s) | ETL Listed |

Controller

| | |
|-------------------|--|
| Display Type | Microprocessor, Digital |
| Alarms | High/Low Temp, Power Failure, Low Battery |
| Alarm Relay | Yes, Dry Contacts |
| Automatic Restart | Yes, Automatically Restarts After Power Failure |
| Backup Battery | Yes, Only Powers Alarm |

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES



Warranty 1 Year Parts & Labor

Specifications subject to change without notice